

SPLIT 1x1 VERA 3



Includes COLD CATALYST FILTER + ACTIVE CARBON + SILVER ION



MODEL		EW26VERA3R32	EW35VERA3R32	EW52VERA3R32	EW71VERA3R32
	IN.	EW26VERA3R32-I	EW35VERA3R32-I	EW52VERA3R32-I	EW71VERA3R32-I
	OUT.	EW26VERA3R32-O	EW35VERA3R32-O	EW52VERA3R32-O	EW71VERA3R32-O
Power Supply	V,P,HZ	220-240V (1 Phase ~ 50Hz) / Outdoor unit			
PERFORMANCE					
Cooling capacity	Capacity (min. - max.)	kW 2,6 (0,9 - 3,39)	3,5 (1,11 - 4,16)	5,2 (0,34 - 5,83)	7,1 (2,08 - 7,95)
		Btu/h 9.000 (3.100~11.600)	12.000 (3.800~14.200)	18.000 (11.157~19.900)	24.000 (7.100~27.000)
	Consumption (min. - max.)	W 799 (100~1.240)	1.213 (130~1.580)	1.500 (560~2.050)	2.600 (420~3150)
	SEER	- 6,2	6,1	7,4	6,1
Heating capacity	Capacity (min. - max.)	kW 2,3	3,8 (1,08 - 4,22)	5,56 (3,1 - 5,85)	7,3 (1,61 - 7,95)
		Btu/h 10.000 (2.800~11.500)	13.000 (3.700~14.400)	19.000 (10.580~19.960)	25.000 (5.500~27.000)
	Consumption (min. - max.)	W 789 (120~1.200)	1.088 (100~1.680)	1.570 (780~2.000)	2.400 (300~2.750)
	SCOP	- 4	4	4	4
Energy class	Heat	A+	A+	A+	A+
FEATURES					
Indoor unit	Sound power	dB(A) 50	55	56	59
	Sound pressure	dB(A) 38/31/25/21	40,5/34,5/25/22	42,5/36/26/25	44,5/42/36/28
	Air flow	m3/h 434,8/333/259	540/430/314	840/680/540	980/817/662
	Selectable temp. range	°C 16 ~ 31	16 ~ 31	16 ~ 31	16 ~ 31
Outdoor unit	Sound power	dB(A) 60	63	63	67
	Sound pressure	dB(A) 55,5	56	56	59
	Air flow	m3/h 1.750	1.800	2.100	3.500
	Hot/Cold operation temp.	°C (-15 ~ 50) / (-15 ~ 30)	(-15 ~ 50) / (-15 ~ 30)	(-15 ~ 50) / (-15 ~ 30)	(-15 ~ 50) / (-15 ~ 30)
Compressor		GMCC	GMCC	GMCC	
Refrigerant	Type/Charge	R32/Kg 0,55	0,55	1,08	1,42
	Supplementary charge>5	g/m 12	12	12	24
DIMENSIONS AND WEIGHT					
Indoor unit	Net dimensions (WxHxD)	mm 715x285x194	805x285x194	957x302x213	1040x327x220
	Gross dimensions (WxHxD)	mm 780x365x270	870x365x270	1035x385x295	1120x405x315
	Net / Gross weight	kg 7,0/9,1	7,6/9,7	10,1/13	12,3/15,8
Outdoor unit	Net dimensions (WxHxD)	mm 720x495x270	720x495x270	805x554x330	890x673x342
	Gross dimensions (WxHxD)	mm 835x540x300	835x540x300	915x615x370	995x740x398
	Net / Gross weight	kg 23,2/25	23,2/25	32,7/35,4	42,9/45,9
CONNECTIONS					
Refrigerant pipe	Liquid-Gas	in. 1/4" - 3/8"	1/4" - 3/8"	1/4" - 1/2"	3/8" - 5/8"
	Max. length	m 25	25	30	50
	Max. unevenness	m 10	10	20	25
Electric connections	Power Supply	mm 2 x 2,5 + T	2 x 2,5 + T	2 x 2,5 + T	2 x 2,5 + T
	Interconnection	mm 4 x 2,5 + T	4 x 2,5 + T	4 x 2,5 + T	4 x 2,5 + T
EAN code	I.U. + O.U. set	8435483832848	8435483832831	8435483847408	8435483847439
	Compatible WiFi module (USBWIFI01)			8435483801844	

NOTE

Capacity data under standard conditions. Actual data will vary depending on where the equipment is installed and how it is used. Sound pressure values are measured at a distance of 1m in a semi-anechoic chamber. The dimensions of the electrical wiring are approximate, it must be calculated based on the conditions of the installation itself.

EWASSER reserves the right to modify models and technical data without prior notice. Valid information except typographical or printing error.